



Quality You Can Rely On



2x12V/160Ah Maintenance-free
battery Built-in Charger (for non-EU)
or 24V/160Ah Lead-acid battery (for EU)

PTE18L

Capacity **1800** kg / **4000** lbs!



Unique 36V system
3x12V/85Ah Maintenance-free battery
Optional Built-in Charger
Easy side-battery-replacement

PTE20X

Capacity **2000** kg / **4400** lbs!



PTE18L



Special design
Easy entry & exit to
the pallet



Built-in Charger(for non-EU)
Big capacity Maintenance
-free Battery



Easy-maintenance
Robust and Reliable
Design



Bigger ground clearance
(for non-EU)
Standard suspension castors
for EU, Optional for non-EU
market



Long tiller design for
ergonomics and safety



PTE20X



High Performance side-battery-replacement



Integrated hydraulic Pump

Bigger Steering Wheel for stability



Long tiller design for ergonomics and safety



Optional Battery Charger



Robust and reliable design

PTE18L

1.1	Manufacturer's type designation		PTE18L
1.2	Load Capacity / rated load	Q(t)	1.8
1.3	Service weight	Kg	415
1.4	Height, lowered	mm	75
1.5	Overall length	mm	1790
1.6	Overall width	mm	729
1.7	Distance between fork-arms	mm	685
1.8	Turning radius	mm	1525 ¹⁾
1.9	Travel speed, laden/ unladen	Km/h	5.0/5.2

1) Load section lowered:+62mm

PTE20X

1.1	Manufacturer's type designation		PTE20X	
1.2	Load Capacity / rated load	Q(t)	2.0	
1.3	Service weight	Kg	405	410
1.4	Height, lowered	mm	85	83
1.5	Overall length	mm	1750	1820
1.6	Overall width	mm	729	
1.7	Distance between fork-arms	mm	540/685	
1.8	Turning radius	mm	1610	1680
1.9	Travel speed, laden/ unladen	Km/h	5.8/5.5	